

RT 857 - Especificações técnicas



Description

RT 857 é um pneu apropriado para aplicações para o trabalho do terreno. A carcaça robusta garante uma ótima durabilidade e excelente tração. O composto de borracha do piso do pneu é caracterizado por uma resistência elevada a todos os tipos de corte e restolho.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

Version	STANDARD
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1476
Static Loaded Radius (mm)	656
Rolling Circumference (mm)	4398
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 13
ECE	E4-106R-001394
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10LT	1845	2145	2450	2750	3050	3350
10HT	1475	1715	1955	2195	2435	2675

Printed on 17/09/2024 14:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..