

## SAND KING - Especificações técnicas



### Description

SAND KING é um pneu com desenho do piso por blocos, concebido particularmente para reboques para aplicações de transporte. Assegura uma tração excelente em superfícies arenosas junto com um ótimo contacto com o terreno.

### UM

International Standard

### Construction

✚ BIAS

### Machinery

Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	425 / 90 D - 21 (15.00 - 21)

# Dimensions International Standard

Ply Rating	18
Section Width (mm)	420
Overall Diameter (mm)	1332
Rim Rec	11.25

## Load capacity (Kg)

km/h / bar	6.55
64	4940

Printed on 13/03/2024 08:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..