

SAND KING - Especificações técnicas



Description

SAND KING é um pneu com desenho do piso por blocos, concebido particularmente para reboques para aplicações de transporte. Assegura uma tração excelente em superfícies arenosas junto com um ótimo contacto com o terreno.

UM

US Standard

Construction

✚ BIAS

Machinery

Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions US Standard

Usa code	94032945
Ply Rating	12
Section Width (inch)	8.5
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	97.3
Rim Rec	5.50 F SDC
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	90
40 LS	3000

Printed on 13/03/2024 11:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..