

SAND KING - Especificações técnicas



Description

SAND KING é um pneu com desenho do piso por blocos, concebido particularmente para reboques para aplicações de transporte. Assegura uma tração excelente em superfícies arenosas junto com um ótimo contacto com o terreno.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	10
Section Width (mm)	215
Overall Diameter (mm)	820
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2471
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005309

Load capacity (Kg)

km/h / bar	5.20
65 LS	1215

Printed on 26/04/2024 06:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..