

## SAND STAR - Especificações técnicas



### Description

SAND STAR é um pneu com desenho do piso por blocos, concebido particularmente para reboques. Assegura uma tração excelente em superfícies arenosas junto com um ótimo contacto com o terreno, reduzindo também a compactação do solo.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Reboque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 9.00 - 13 |
| LI/SS     | 119 A8    |

## Dimensions US Standard

|                         |                 |
|-------------------------|-----------------|
| Usa code                | 94031726        |
| Ply Rating              | 10              |
| Section Width (inch)    | 9.6             |
| Overall Diameter (inch) | 30.9            |
| Rim Rec                 | 5.50 F          |
| Rim Alt                 | 5.50 WB         |
| ECE                     | E11-106R-005263 |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 48   |
| 25 FR LLV | 3000 |

Printed on 23/04/2024 14:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..