

SIERRA MAX PRO - Especificações técnicas



Description

O SIERRA MAX PRO é o pneu BKT ideal para veículos todo-terreno em aplicações fora da estrada, incluindo corridas lado a lado. A sua construção radial e pegada especial mais larga garantem uma experiência com menos percalços bem como tração lateral e frontal otimizada. As porcas robustas especiais foi desenhadas especificamente para oferecem excelente tração e aderência firme ao terreno. Estas características resultam numa experiência de condução extremamente confortável, em segurança e controlo. O SIERRA MAX PRO garante excelente desempenho em qualquer tipo de terreno, do terreno compactado à terra batida.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Veículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 8 R 12
LI/SS	43 N

Dimensions US Standard

Usa code	94067077
Section Width (inch)	7.9
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.3
Rolling Circumference (inch)	73.2
Rim Rec	6.5
Star Rating	***
ECE	E11-75R-005088

Load capacity (lbs)

mph / psi	7
87	340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 11:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..