

## SIERRA MAX - Especificações técnicas



### Description

SIERRA MAX é o pneu BKT para aplicações todo-o-terreno como para prados e jardins. Graças à sua construção radial, o pneu proporciona uma condução consideravelmente mais suave e mais confortável, mesmo em terrenos extremos, como o deserto ou as superfícies terrosas e rochosas. O desenho especial do piso do pneu e o seu cunho mais largo conferem uma tração anterior e lateral única.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Veículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 9 R 14
LI/SS	50 N

## Dimensions International Standard

Section Width (mm)	230
Overall Diameter (mm)	700
Static Loaded Radius (mm)	316
Rolling Circumference (mm)	2070
Rim Rec	7.00
Star Rating	***
ECE	E11-75R-005099

## Load capacity (Kg)

km/h / bar	0.50
140	190

Printed on 27/04/2024 07:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..