

## SKID POWER HD (A) - Especificações técnicas

### Description

SKID POWER HD (A) foi projetado para pás skid steer nas aplicações da construção civil. O pneu destaca-se pelo piso super profundo e pela proteção dos flancos, que asseguram uma resistência a cortes e rasgões, bem como uma duração extraordinária. SKID POWER HD (A) é o pneu ideal para superfícies terrosas e utilizações pesadas.



### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Minicarregadora

Version	IMPLEMENT
Type	TL
Tyre Size	27 X 10.5 - 15
LI/SS	105 A8

## Dimensions US Standard

Usa code	94056026
Ply Rating	8
Section Width (inch)	10.1
Overall Diameter (inch)	26.9
Static Loaded Radius (inch)	12.8
Rolling Circumference (inch)	80.2
Rim Rec	8 LB
ECE	E11-106R-003539

## Load capacity (lbs)

mph / psi	61
25	2040

Printed on 27/04/2024 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..