

SKID POWER HD (A) - Especificações técnicas

Description

SKID POWER HD (A) foi projetado para pás skid steer nas aplicações da construção civil. O pneu destaca-se pelo piso super profundo e pela proteção dos flancos, que asseguram uma resistência a cortes e rasgões, bem como uma duração extraordinária. SKID POWER HD (A) é o pneu ideal para superfícies terrosas e utilizações pesadas.



UM

International Standard

Construction

 BIAS

Machinery

Industrial: Minicarregadora

Version	IMPLEMENT
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	131 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	394
Overall Diameter (mm)	838
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2563
Rim Rec	13.00
ECE	E11-106R-003018

Load capacity (Kg)

km/h / bar	4.10
40	1950

Printed on 27/04/2024 04:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..