

## SKID POWER SK - Especificações técnicas



### Description

SKID POWER SK foi especialmente desenvolvido para pás skid steer nas aplicações para o segmento das construções. Os cordões de proteção do flanco e da jante, bem como o piso super profundo fornecem um ciclo de vida prolongado do pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Minicarregadora

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5
LI/SS	138 A2

## Dimensions US Standard

Usa code	94047109
Ply Rating	12
Section Width (inch)	10.6
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25

## Load capacity (lbs)

mph / psi	90
5	5240
10	4135
15	3815

Printed on 24/04/2024 22:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..