

SKID POWER SK - Dados técnicos



Description

SKID POWER SK foi especialmente desenvolvido para pás skid steer nas aplicações para o segmento das construções. Os cordões de proteção do flanco e da jante, bem como o piso super profundo fornecem um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicarregadora

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	STANDARD	94017225		10	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94017201		8	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94047109	138 A2	12	8.25		10.6	30.5	14	90	TL	
10 - 16.5	IMPLEMENT	94055708	116 A8	8	8.25		10.6	30.5	14	90	TL	E11-106R-003543
10 - 16.5	IMPLEMENT	94055715	120 A8	10	8.25		10.6	30.5	14	90	TL	E11-106R-003544
12 - 16.5	IMPLEMENT	94055746	130 A8	12	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	94055722	125 A8	10	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003545
12 - 16.5	STANDARD	94017249		10	9.75		12.3	32.5	14.8	95.8	TL	
12 - 16.5	STANDARD	94017263		12	9.75		12.3	32.5	14.8	95.8	TL	

Printed on 24/04/2024 15:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..