

## SKID POWER - Especificações técnicas



### Description

SKID POWER foi desenvolvido para pás skid steer nas aplicações da construção civil e mostra uma tração excelente junto com propriedades avançadas de autolimpagem. O pneu destaca-se pelo piso super profundo junto com uma proteção especial dos flancos, assegurando uma resistência excelente a cortes e rasgões, bem como uma duração extraordinária. SKID POWER é o pneu ideal para superfícies terrosas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Minicarregadora

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

## Dimensions US Standard

Usa code	94017133
Ply Rating	10
Section Width (inch)	12
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	95.4
Rim Rec	9.75

## Load capacity (lbs)

mph / psi	65
5	5600
10	4420
15	4090

Printed on 20/04/2024 00:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..