

SKID POWER - Especificações técnicas



Description

SKID POWER foi desenvolvido para pás skid steer nas aplicações da construção civil e mostra uma tração excelente junto com propriedades avançadas de autolimpagem. O pneu destaca-se pelo piso super profundo junto com uma proteção especial dos flancos, assegurando uma resistência excelente a cortes e rasgões, bem como uma duração extraordinária. SKID POWER é o pneu ideal para superfícies terrosas.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicarregadora

Version	IMPLEMENT
Type	TL
Tyre Size	12 - 16.5
LI/SS	125 A8

Dimensions US Standard

Usa code	94055678
Ply Rating	10
Section Width (inch)	12
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	95.4
Rim Rec	9.75
ECE	E11-106R-003535

Load capacity (lbs)

mph / psi	65
25	3640

Printed on 19/04/2024 15:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..