

## SM 54 L4S - Dados técnicos



### Description

O SM 54 (L-4S) foi especialmente desenhado para manipuladores de contentores vazios e empilhadores em aplicações intermodais/logísticas. Apresenta alta estabilidade em modo de elevação, assim como um desenho do piso profundo e suave, dotando-o de uma excelente resistência ao corte, por forma a garantir ao pneu um ciclo de vida prolongado.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Reach Stacker

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.00 - 25	INDUSTRIAL	L4S	28	11.25/2.0	13.00/2.0	430	1470	676	4354	TL
16.00 - 25	INDUSTRIAL	L4S	32	11.25/2.0	13.00/2.0	430	1470	676	4354	TL
18.00 - 33	PORT INDUSTRIAL	L4S	36	13.00/2.5		535	1895	840	5609	TL
18.00 - 33	PORT INDUSTRIAL	L4S	40	13.00/2.5		535	1895	840	5609	TL

Printed on 02/12/2023 13:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..