

SM 54 M IND-4S - Especificações técnicas



Description

SM 54 M IND-4S é uma versão modificada do SM 54. O perfil mais baixo do piso se mostra como área de contacto mais vasta e garante um ciclo de vida prolongado. O pneu foi especificadamente projetado para unidades de movimentação de contentores vazios e reach stacker nas aplicações intermodais e de logística. O pneu destaca-se pela elevada estabilidade em modalidade de levantamento, com desenho do piso do pneu profundo ou liso, fornecendo uma resistência excelente aos cortes.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94050215
Ply Rating	40
Overall Width (inch)	21.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	220.8
Rim Rec	13.00/2.5
TRA Code	IND-4S

Load capacity (lbs)

mph / psi	145
5	59525

Printed on 23/04/2024 09:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..