

SM 54 M IND-4S - Dados técnicos



Description

SM 54 M IND-4S é uma versão modificada do SM 54. O perfil mais baixo do piso se mostra como área de contacto mais vasta e garante um ciclo de vida prolongado. O pneu foi especificadamente projetado para unidades de movimentação de contentores vazios e reach stacker nas aplicações intermodais e de logística. O pneu destaca-se pela elevada estabilidade em modalidade de levantamento, com desenho do piso do pneu profundo ou liso, fornecendo uma resistência excelente aos cortes.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	INDUSTRIAL	94055791	L4S	40	13.00/2.5	15.00/2.5	20.8	65	29.5	192.1	TL
18.00 - 33	PORT INDUSTRIAL	94050215	IND-4S	40	13.00/2.5		21.1	74.6	33.1	220.8	TL

Printed on 20/04/2024 18:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..