

SM 55 L5S - Especificações técnicas



Description

SM 55 (L-5S) é um pneu de lonas cruzadas, ideal para as operações nas minas subterrâneas. O piso é realizado com um composto de borracha especial, resistente a cortes e rasgões e é caracterizado por uma profundidade extra L-5S. Isto significa tempos reduzidos de paragem da máquina, garantindo uma vida prolongada do pneu. O pneu também está disponível em versão "steel belted" com cintos em aço.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper de baixo perfil • Veículo para minas subterrâneas

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	517
Overall Diameter (mm)	1665
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	5118
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	L5S

Load capacity (Kg)

km/h / bar	6.50
10	13600

Printed on 27/04/2024 09:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..