

## SM 55 L5S - Especificações técnicas



### Description

SM 55 (L-5S) é um pneu de lonas cruzadas, ideal para as operações nas minas subterrâneas. O piso é realizado com um composto de borracha especial, resistente a cortes e rasgões e é caracterizado por uma profundidade extra L-5S. Isto significa tempos reduzidos de paragem da máquina, garantindo uma vida prolongada do pneu. O pneu também está disponível em versão "steel belted" com cintos em aço.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

OTR: Dumper de baixo perfil • Veículo para minas subterrâneas

Version	ARASHIELD
Type	TL
Tyre Size	29.5 - 29

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	755
Overall Diameter (mm)	2020
Static Loaded Radius (mm)	882
Rolling Circumference (mm)	6021
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
TRA Code	L5S
Tread Depth	104

## Load capacity (Kg)

	km/h / bar	6.25
	10	23600
	15	20530
	25	18880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/04/2025 05:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..