

SM 55 L5S - Especificações técnicas



Description

SM 55 (L-5S) é um pneu de lonas cruzadas, ideal para as operações nas minas subterrâneas. O piso é realizado com um composto de borracha especial, resistente a cortes e rasgões e é caracterizado por uma profundidade extra L-5S. Isto significa tempos reduzidos de paragem da máquina, garantindo uma vida prolongada do pneu. O pneu também está disponível em versão "steel belted" com cintos em aço.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper de baixo perfil • Veículo para minas subterrâneas

| | |
|-----------|------------|
| Version | ARASHIELD |
| Type | TL |
| Tyre Size | 35/65 - 33 |

Dimensions International Standard

| | |
|-----------------------|-----------|
| Ply Rating | 48 |
| Overall Width (mm) | 920 |
| Overall Diameter (mm) | 2085 |
| Rim Rec | 28.00/3.5 |
| TRA Code | L5S |

Load capacity (Kg)

| | |
|------------|-------|
| km/h / bar | 7.25 |
| 10 | 29000 |

Printed on 27/04/2024 10:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..