

SNOW - RIDE (B) - Especificações técnicas

Description

SNOW-RIDE é especialmente apropriado para aplicações na estrada em condições inverniais com pás carregadoras e tratores de esteira. O pneu destaca-se pela tração excelente e é ideal para operações na neve e no gelo. O desenho especial do piso do pneu elimina os riscos de deslizamento.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Trator de esteira • Carregadora



Version	STANDARD
Type	TL
Tyre Size	15.5 - 25

Dimensions International Standard

Ply Rating	12
Section Width (mm)	395
Overall Diameter (mm)	1280
Static Loaded Radius (mm)	569
Rolling Circumference (mm)	3818
Rim Rec	12.00/1.3
TRA Code	L2

Load capacity (Kg)

km/h / bar	4.00
10	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 15:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..