

## SNOW - RIDE (B) - Especificações técnicas

### Description

SNOW-RIDE é especialmente apropriado para aplicações na estrada em condições inverniais com pás carregadoras e tratores de esteira. O pneu destaca-se pela tração excelente e é ideal para operações na neve e no gelo. O desenho especial do piso do pneu elimina os riscos de deslizamento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Trator de esteira • Carregadora



Version	STANDARD
Type	TL
Tyre Size	16.9 - 24

## Dimensions International Standard

Ply Rating	12
TKPH	1
Section Width (mm)	429
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3930
SRI (mm)	625
Rim Rec	DW 15 L
Rim Alt	DW 14 L

## Load capacity (Kg)

km/h / bar	2.60
40	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 16:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..