

ST 180 - Especificações técnicas



Description

ST 180 é um pneu para ser utilizado principalmente na estrada, concebido para aplicações de transporte com reboques e implementos agrícolas. O desenho específico do piso reduz o desgaste, garantindo um ciclo de vida longo do pneu. ST 180 está disponível em inúmeras versões: numa versão "aramid belted", com cintos em aramida, para uma maior resistência à perfuração, enquanto a versão "special" proporciona uma elevada resistência aos cortes e furos.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	5.00 - 10

Dimensions US Standard

Usa code	94043002
Ply Rating	6
Section Width (inch)	5.6
Overall Diameter (inch)	20.9
Rim Rec	3.5
ECE	E4-54R-0030484

Load capacity (lbs)

mph / psi	45
62	860

Printed on 08/05/2024 21:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..