

## ST 180 - Especificações técnicas



### Description

ST 180 é um pneu para ser utilizado principalmente na estrada, concebido para aplicações de transporte com reboques e implementos agrícolas. O desenho específico do piso reduz o desgaste, garantindo um ciclo de vida longo do pneu. ST 180 está disponível em inúmeras versões: numa versão "aramid belted", com cintos em aramida, para uma maior resistência à perfuração, enquanto a versão "special" proporciona uma elevada resistência aos cortes e furos.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	ST 165/80 D 13 (A 78 - 13)

## Dimensions International Standard

<b>Ply Rating</b>	4
<b>Section Width (mm)</b>	156
<b>Overall Diameter (mm)</b>	597
<b>Static Loaded Radius (mm)</b>	272
<b>Rolling Circumference (mm)</b>	1746
<b>Rim Rec</b>	4½ J
<b>Rim Alt</b>	5 J ; 5½ J ; 6 J

## Load capacity (Kg)

km/h / bar	2.50
40	450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/02/2025 16:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..