

ST 180 - Dados técnicos



Description

ST 180 é um pneu para ser utilizado principalmente na estrada, concebido para aplicações de transporte com reboques e implementos agrícolas. O desenho específico do piso reduz o desgaste, garantindo um ciclo de vida longo do pneu. ST 180 está disponível em inúmeras versões: numa versão "aramid belted", com cintos em aramida, para uma maior resistência à perfuração, enquanto a versão "special" proporciona uma elevada resistência aos cortes e furos.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.80 - 8	STANDARD	94008759	6	3.75 - I - 55	3.75 - I - 70	4.8	16.5	0	0	TL	
5.70 - 8	STANDARD	94008797	8	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	5.6	18.7	0	0	TL	
5.70 - 8	STANDARD	94027897	6	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	5.6	18.7	0	0	TL	
6.00 - 9	STANDARD	94008827	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TT	E4-54R-0022804
6.00 - 9	STANDARD	94038343	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022804
6.00 - 9	STANDARD	94038350	10	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022805
6.00 - 9	STANDARD	94026623	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TT	E4-54R-0022806
6.00 - 9	STANDARD	94038367	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	6.5	21.3	0	0	TL	E4-54R-0022806
5.00 - 10	STANDARD	94043002	6	3.5		5.6	20.9	0	0	TL	E4-54R-0030484
ST 165/80 D 13 (A 78 - 13)	STANDARD	94018079	4	4½ J	5 J ; 5½ J ; 6 J	6.1	23.5	10.7	68.7	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018086	4	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018093	6	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	94018109	8	5 J	4½ J ; 5½ J ; 6 J	6.9	24.4	11.3	72.6	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018116	4	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018123	6	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	94018130	8	5 J	5½ J ; 6 J ; 6½ J	7.6	26.3	12.3	79.3	TL	
ST 205/65 D 14 (F 65 - 14)	STANDARD	94018147	6	5 J	5½ J	7.5	24.4	11.5	73.8	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	94018161	4	6 J	5 J ; 5½ J ; 6 J	7.9	26.9	12.5	80.7	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	94018178	6	6 J	5 J ; 5½ J ; 6 J	7.9	26.9	12.5	80.7	TL	
ST 215/75 D 14 (G 78 - 14)	ARAMID BELTED	94053018	10	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 215/75 D 14 (G 78 - 14)	SPECIAL	94052943	10	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 215/75 D 14 (G 78 - 14)	STANDARD	94018208	6	6 J	5½ J ; 6½ J ; 7 J	8.1	26.9	12.6	81.6	TL	
ST 205/65 D 15 (F 65 - 15)	STANDARD	94018154	6	6 J	5½ J ; 6½ J	7.6	25.5	11.9	76.2	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	94018185	4	5½ J	5 J ; 6 J ; 7 J	7.7	27.6	12.9	82.8	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	94018192	6	5½ J	5 J ; 6 J ; 7 J	7.7	27.6	12.9	82.8	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	94018215	6	6 J	5½ J ; 6½ J ; 7 J	8.5	28.7	13.3	85.7	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	94018222	8	6 J	5½ J ; 6½ J ; 7 J	8.5	28.7	13.3	85.7	TL	

Printed on 08/05/2024 19:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part,

