

STEER GRIP - Especificações técnicas



Description

STEER GRIP é o equipamento ideal para os eixos direcionais de caminhões basculantes. A larga nervura central com barras do pneu lineares, torna o pneu apropriado para aplicações de rolamento livre, garantindo excelentes prestações, tanto em condições de terreno molhado como seco fora da estrada. O especial composto de borracha do piso foi realizado para associar uma ótima resistência com o desgaste e resistência aos cortes e lacerações, enquanto a carcaça robusta assegura um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Camião basculante

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	310
Overall Diameter (mm)	1248
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3785
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 23/04/2024 13:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..