

## SUPER SAND - Especificações técnicas



### Description

SUPER SAND é apropriado particularmente para reboques que operam em superfícies arenosas em condições climáticas quentes. O pneu destaca-se pela elevada capacidade de flutuação e é ideal para todas as operações que exigem um nível elevado de tratamento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	16.00 - 20

## Dimensions US Standard

Usa code	94048359
Ply Rating	16
Section Width (inch)	16.3
Overall Diameter (inch)	51.4
Rim Rec	10.00 W

## Load capacity (lbs)

mph / psi	36
30	8050

Printed on 10/04/2024 20:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..