

## SUPER TRAX HD - Especificações técnicas



### Description

SUPER TRAX HD foi especificadamente projetado para empilhadores utilizados na movimentação de mercadoria com serviço pesado, incluídas as aplicações no porto e nas minas. O piso do pneu extra profundo foi realizado com um composto de borracha excepcional, resistente ao desgaste, que assegura uma vida operacional prolongada. SUPER TRAX HD destaca-se pela carcaça robusta e o flanco reforçado do pneu, que se traduzem numa excelente estabilidade e numa boa capacidade de manobra em fase de levantamento. O especial bordo de proteção da jante protege o pneu na aba da jante de esvaziamentos e danos.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	220
Overall Diameter (mm)	715
Static Loaded Radius (mm)	332
Rolling Circumference (mm)	2169
Rim Rec	7.00
Rim Alt	7 BD

## Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	3900
25 STEER WHEEL	3000
10 OTHER VEHICLES	3900
25 OTHER VEHICLES	3000
STATIC SIDE LOADER	4530

Printed on 17/04/2024 20:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..