

TR 126 - Especificações técnicas



Description

TR 126 foi desenvolvido para tratores pequenos nas operações para trabalhar a terra. Os blocos profundos e o desenho especial do piso proporcionam uma tração excelente e uma ótima capacidade de carga, que se traduzem em prestações muito elevadas em todas as condições operacionais.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator pequeno

Version	STANDARD
Type	TL
Tyre Size	7 - 14
LI/SS	72 A6

Dimensions International Standard

Ply Rating	4
Section Width (mm)	170
Overall Diameter (mm)	690
Static Loaded Radius (mm)	320
Rolling Circumference (mm)	2070
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-003356
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.60
30	355

Printed on 24/04/2024 06:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..