

## TR 128 - Especificações técnicas



### Description

TR 128 foi especialmente projetado para tratores compactos e cultivadores rotativos. O desenho largo e profundo das barras e o composto de borracha especial resistente aos cortes e lacerações asseguram uma vida prolongada do pneu. TR 128 destaca-se pela máxima tração no terreno molhado.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Cultivador rotativo • Veiculo universal

Version	STANDARD
Type	TT
Tyre Size	6.00 - 12
LI/SS	72 A8

## Dimensions US Standard

Usa code	94045242
Ply Rating	6
Section Width (inch)	6.3
Overall Diameter (inch)	25
Static Loaded Radius (inch)	11.7
Rolling Circumference (inch)	75.8
Rim Rec	4.00 E
Rim Alt	4.00 E DT
ECE	E11-106R-003479

## Load capacity (lbs)

mph / psi	38
25	785

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 20:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..