# TR 135 - Especificações técnicas

## Description

TR 135 é muito apropriado para tratores nas aplicações para trabalhar o solo. A carcaça reforçada e o composto de borracha especial resistente aos cortes e lacerações asseguram uma vida prolongada do pneu. Ótimas performances em tema de tração, propriedades de autolimpagem e capacidade de carga são as características chave que tornam o TR 135 o pneu ideal também perante condições mais difíceis do terreno.

## UM

US Standard

## Construction

BIAS

## Machinery

Agricultura: Trator
Industrial: Reboque

| | |
|---|---|
| **Version** | HD |
| **Type** | TT |
| **Tyre Size** | 16.9 - 24 |
| **LI/SS** | 129 A8 |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94038244 |
| **Ply Rating** | 8 |
| **Section Width (inch)** | 16.9 |
| **Overall Diameter (inch)** | 52.6 |
| **Static Loaded Radius (inch)** | 24.1 |
| **Rolling Circumference (inch)** | 154.5 |
| **Rim Rec** | W 15 L |
| **Rim Alt** | W 14 L |
| **TRA Code** | R1 |

## Load capacity (lbs)

| mph / psi | 24 |
|---|---|
| **25** | 4080 |

Printed on 28/04/2024 23:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..