

TR 138 - Especificações técnicas



Description

TR 138 foi especialmente projetado para levantadores telescópicos e retroescavadoras. O pneu é muito apropriado para trabalhar o solo e nas aplicações de irrigação. Uma tração superior, propriedades de autolimpagem e estabilidade são as características chave que tornam TR 138 o pneu ideal também perante condições mais difíceis do terreno.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Retroescavadora • Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	17.5L - 24
LI/SS	151 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1290
Static Loaded Radius (mm)	576
Rolling Circumference (mm)	3836
Rim Rec	DW 15L
Rim Alt	DW 14L
ECE	E11-106R-005232

Load capacity (Kg)

km/h / bar	40
2.6	3450

Printed on 27/04/2024 11:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..