

TR 138 - Especificações técnicas



Description

TR 138 foi especialmente projetado para levantadores telescópicos e retroescavadoras. O pneu é muito apropriado para trabalhar o solo e nas aplicações de irrigação. Uma tração superior, propriedades de autolimpagem e estabilidade são as características chave que tornam TR 138 o pneu ideal também perante condições mais difíceis do terreno.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Retroescavadora • Levantador telescópico

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 17.5L - 24 |
| LI/SS | 151 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94061877 |
| Ply Rating | 12 |
| Section Width (inch) | 17.7 |
| Overall Diameter (inch) | 50.8 |
| Static Loaded Radius (inch) | 22.7 |
| Rolling Circumference (inch) | 151 |
| Rim Rec | DW 15L |
| Rim Alt | DW 14L |
| ECE | E11-106R-005232 |

Load capacity (lbs)

| | | |
|--|-----------|------|
| | mph / psi | 25 |
| | 39 | 7605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/10/2024 00:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..