

TR 144 - Especificações técnicas



Description

TR 144 é apropriado para ser utilizado com tratores pequenos nas operações para trabalhar a terra. TR 144 garante performances extraordinárias em todas as condições operacionais que exigem uma tração excelente associada a cargas elevadas. TR 144 é também disponível em versão especial, muito apropriada para as operações de serviço pesadas.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator pequeno

Version	STANDARD
Type	TT
Tyre Size	8 - 16
LI/SS	79 A8

Dimensions US Standard

Usa code	94036301
Ply Rating	4
Section Width (inch)	7.9
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	92.2
Rim Rec	6 L ; 6 LB ; 6.00 F
ECE	E11-106R-004323
TRA Code	R1

Load capacity (lbs)

mph / psi	18
25	965

Printed on 19/04/2024 17:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..