

TR 173 - Dados técnicos



Description

TR 173 é um pneu para tratores ideal para terrenos molhados e nos arrozais. El desenho especial do piso proporciona ótimas qualidades de autolimpagem, bem como uma compactação do solo reduzida graças à sua ampla área de contacto.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
8 - 18	STANDARD	R1W	94 A6	6	W 6	W 7 ; 5.50 F	200	841	392	2525		TT	E11-106R-006500
8.3 - 20	STANDARD	R1W	96 A6	6	W 7	W 6	211	890	418	2713		TT	E11-106R-006482
8.3 - 22	STANDARD	R1W	98 A6	6	W 7	W 6	211	940	443	2869		TT	E11-106R-006483
9.5 - 22	STANDARD	R1W	104 A6	6	W 8	W 7	241	997	472	3045		TT	E11-106R-006485
12.4 - 24	STANDARD	R1W	115 A6	6	W 11	W 9 ; W 10	315	1160	541	3509	550	TT	E11-106R-004480
8.3 - 24	STANDARD	R1W	100 A6	6	W 7	W 6	211	995	467	3009		TT	E11-106R-006484
9.5 - 24	STANDARD	R1W	106 A6	6	W 8	W 7	241	1047	493	3238		TT	E11-106R-006486
13.6 - 26	STANDARD	R1W	120 A6	6	W 12	W 11	345	1255	586	3786		TT	E11-106R-003555
14.9 - 28	STANDARD	R1W	130 A6	8	W 13	W 11 ; W 12	385	1367	631	4215		TT	E11-106R-006487
16.9 - 28	STANDARD	R1W	129 A6	6	W 15 L	W 14 L	445	1450	669	4454		TT	E11-106R-006488

Printed on 24/04/2024 07:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..