

## TR 270 - Especificações técnicas



### Description

TR 270 é um pneu para tratores apropriado para aplicações para trabalhar a terra. O pneu foi especialmente projetado para proporcionar máximas prestações em terrenos húmidos e molhados. Perante estas condições do solo, a um pneu é exigida uma adesão superior junto com propriedades avançadas de autolimpagem. TR 270 satisfaz totalmente estas características.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	18.4 - 34
LI/SS	137 A8

## Dimensions US Standard

Usa code	94004843
Ply Rating	8
Section Width (inch)	18.3
Overall Diameter (inch)	66.2
Static Loaded Radius (inch)	30.4
Rolling Circumference (inch)	198
Rim Rec	DW 16 A ; W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003558
TRA Code	R2

## Load capacity (lbs)

mph / psi	20
25	5080

Printed on 08/05/2024 23:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..