

## TR 270 - Dados técnicos



### Description

TR 270 é um pneu para tratores apropriado para aplicações para trabalhar a terra. O pneu foi especialmente projetado para proporcionar máximas prestações em terrenos húmidos e molhados. Perante estas condições do solo, a um pneu é exigida uma adesão superior junto com propriedades avançadas de autolimpagem. TR 270 satisfaz totalmente estas características.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
23.1 - 26	STANDARD	R2	145 A6	8	DW 20 A ; DW 20 B		590	1646	739	4922	TT		
23.1 - 26	STANDARD	R2	149 A6	10	DW 20 A ; DW 20 B		590	1646	739	4922	TT		E11-106R-003620
23.1 - 26	STANDARD	R2	153 A6	12	DW 20 A ; DW 20 B		590	1646	739	4922	TT		E11-106R-004499
23.1 - 26	STANDARD	R2	153 A6	12	DW 20 A ; DW 20 B		590	1646	739	4922	TL		E11-106R-004499
23.1 - 26	STANDARD	R2	156 A6	14	DW 20 A ; DW 20 B		590	1646	739	4922	TT		E11-106R-003617
18.4 - 30	STANDARD	R2	139 A6	8	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	TT		E11-106R-003557
18.4 - 30	STANDARD	R2	139 A6	8	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	TL		E11-106R-003557
18.4 - 30	STANDARD	R2	149 A6	12	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	TT		E11-106R-004121
23.1 - 30	STANDARD	R2	146 A6	8	DW 20 A ; DW 20 B		590	1748	790	5227	TT		
23.1 - 30	STANDARD	R2	151 A6	10	DW 20 A ; DW 20 B		590	1748	790	5227	TT		E11-106R-003622
23.1 - 30	STANDARD	R2	155 A6	12	DW 20 A ; DW 20 B		590	1748	790	5227	TT		E11-106R-004504
18.4 - 34	STANDARD	R2	142 A6	8	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	TT		E11-106R-003558
18.4 - 34	STANDARD	R2	150 A6	12	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	TT	1	E11-106R-004517
23.1 - 34	STANDARD	R2	148 A6	8	DW 20 A ; DW 20 B		590	1850	841	5532	TT		
23.1 - 34	STANDARD	R2	153 A6	10	DW 20 A ; DW 20 B		590	1850	841	5532	TT		E11-106R-003623
23.1 - 34	STANDARD	R2	156 A6	12	DW 20 A ; DW 20 B		590	1850	841	5532	TT		E11-106R-004507
23.1 - 34	STANDARD	R2	160 A6	14	DW 20 A ; DW 20 B		590	1850	841	5532	TT		E11-106R-004510
13.6 - 38	STANDARD	R2	122 A6	6	W12	DW12A , W11	345	1600	0	0	TT		E11-106R-004340
18.4 - 38	STANDARD	R2	143 A6	8	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	TT		E11-106R-003559
18.4 - 38	STANDARD	R2	153 A6	12	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	TT		E11-106R-004511
20.8 - 38	STANDARD	R2	148 A6	8	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	TT	0	E11-106R-003378
20.8 - 38	STANDARD	R2	151 A6	10	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	TT		E11-106R-004512
20.8 - 38	STANDARD	R2	156 A6	12	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	TT		E11-106R-004513
13.6 - 46	STANDARD	R2	125 A6	6	W12	W12A	345	1804	0	0	TT		E11-106R-004343

Printed on 08/05/2024 22:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..