

TR 273 - Especificações técnicas



Description

TR 273 é um pneu para tratores apropriado para aplicações para trabalhar a terra. O pneu foi especialmente projetado para proporcionar máximas prestações em terrenos húmidos e molhados. Perante estas condições do solo, a um pneu é exigida uma adesão superior junto com propriedades avançadas de autolimpagem. TR 273 satisfaz perfeitamente estas características.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	14.9 - 24
LI/SS	128 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	380
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	4044
Rim Rec	W 13
Rim Alt	W 12
ECE	E11-106R-004514
TRA Code	R2

Load capacity (Kg)

km/h / bar	1.80
30	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..