

TR 273 - Especificações técnicas



Description

TR 273 é um pneu para tratores apropriado para aplicações para trabalhar a terra. O pneu foi especialmente projetado para proporcionar máximas prestações em terrenos húmidos e molhados. Perante estas condições do solo, a um pneu é exigida uma adesão superior junto com propriedades avançadas de autolimpagem. TR 273 satisfaz perfeitamente estas características.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	23.1 - 26
LI/SS	149 A8

Dimensions US Standard

Usa code	94039821
Ply Rating	12
Section Width (inch)	23.2
Overall Diameter (inch)	65.2
Static Loaded Radius (inch)	29
Rolling Circumference (inch)	198.9
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003395
TRA Code	R2

Load capacity (lbs)

mph / psi	24
25	7150

Printed on 25/04/2024 20:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..