

TR 313 - Dados técnicos



Description

TR 313 é um pneu para prados e jardinagem, apropriado para aplicações de obras municipais e na manutenção além de com implementos agrícolas, escavadoras de valas e máquinas para a colheita de pomares. A ampla área de contacto garante uma adesão excelente. O pneu TR 313 foi projetado para garantir um nível de estabilidade elevado perante condições operacionais críticas além de propriedades excelentes de autolimpagem.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Máquina para recolha dos frutos • Escavador de valas

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
31 X 15.50 - 15	STANDARD	8	13 LB		370	780	342	2233	TL	E4-106R-002208

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 12:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..