TR 315 - Especificações técnicas

Description

TR 315 é um pneu para prados e jardinagem, apropriado para aplicações de obras municipais e na manutenção além de para trabalhar a terra. O pneu é ideal para ser utilizado com implementos agrícolas, escavadoras de valas e máquinas para a colheita de pomares. TR 315 mostra uma área ampla de contacto que fornece uma adesão excelente junto além de propriedades excelentes de autolimpagem com uma estabilidade extraordinária perante qualquer condição.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Implementos agrícolas • Maquina para recolha dos frutos • Escavador de valas

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	155
Overall Diameter (mm)	408
Static Loaded Radius (mm)	182
Rolling Circumference (mm)	1183
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90
ECE	E4-106R-002175

Load capacity (Kg)

km/h / bar	2.90
15	355

Printed on 25/04/2024 23:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..