

## TR 317 - Especificações técnicas



### Description

TR 317 é apropriado para aplicações de obras municipais e na manutenção além de trabalhar a terra com implementos agrícolas, escavadoras de valas e máquinas para a colheita de pomares. O pneu TR 317 mostra uma área ampla de contacto que fornece uma adesão excelente e uma estabilidade extraordinária perante qualquer condição além de propriedades excelentes de autolimpagem.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Máquina para recolha dos frutos • Escavador de valas

Version	HD
Type	TL
Tyre Size	18 X 8.50 - 8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	215
Overall Diameter (mm)	450
Static Loaded Radius (mm)	198
Rolling Circumference (mm)	1305
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90

## Load capacity (Kg)

km/h / bar	2.30
15	475

Printed on 27/04/2024 19:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..