

TR 317 - Dados técnicos



Description

TR 317 é apropriado para aplicações de obras municipais e na manutenção além de trabalhar a terra com implementos agrícolas, escavadoras de valas e máquinas para a colheita de pomares. O pneu TR 317 mostra uma área ampla de contacto que fornece uma adesão excelente e uma estabilidade extraordinária perante qualquer condição além de propriedades excelentes de autolimpagem.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Máquina para recolha dos frutos • Escavador de valas

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	HD	94045884	6	7.00 I - 55 ; I - 70 ; I - 90		8.5	17.7	7.8	51.4	TL	
18 X 8.50 - 8	STANDARD	94038879	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	17.7	7.8	51.4	TL	E11-106R-003495

Printed on 12/08/2024 15:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..