

TR 318 - Especificações técnicas



Description

TR 318 foi projetado especialmente para pulverizadores e implementos agrícolas. As barras com ângulo duplo, asseguram uma tração excelente e uma comodidade de condução extraordinária. TR 318 proporciona ainda ótimas qualidades de autolimpagem.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Implementos agrícolas • Pulverizador agrícola

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 26 X 10.00 - 12 |
| LI/SS | 107 A3 |

Dimensions US Standard

| | |
|-------------------------|-----------------|
| Usa code | 94052127 |
| Ply Rating | 8 |
| Section Width (inch) | 10.4 |
| Overall Diameter (inch) | 26.6 |
| Rim Rec | 8.5 |
| ECE | E11-106R-004522 |

Load capacity (lbs)

| mph / psi | 54 |
|-----------|------|
| 10 | 2150 |

Printed on 20/04/2024 07:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..