

TR 387 - Especificações técnicas



Description

TR 387 é um pneu agro-industrial, apropriado para reboques para canas-de-açúcar e compactadores. O pneu destaca-se pela elevada capacidade de carga e está disponível em várias versões, com vista a atender às exigências específicas dos utilizadores em termos de resistência a cortes e rasgões, operações de serviço pesado e duração. A versão "dual bead", de talão duplo, é apropriada particularmente para tratores industriais e operações de transporte com reboques.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	18.4 - 26
LI/SS	142 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	485
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4150
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004638
TRA Code	R3

Load capacity (Kg)

km/h / bar	1.80
30	2650

Printed on 25/04/2024 11:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..