

TR 387 - Especificações técnicas



Description

TR 387 é um pneu agro-industrial, apropriado para reboques para canas-de-açúcar e compactadores. O pneu destaca-se pela elevada capacidade de carga e está disponível em várias versões, com vista a atender às exigências específicas dos utilizadores em termos de resistência a cortes e rasgões, operações de serviço pesado e duração. A versão "dual bead", de talão duplo, é apropriada particularmente para tratores industriais e operações de transporte com reboques.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Reboque

Industrial: Compactador

Version	HD
Type	TT
Tyre Size	18.4 - 30 (15 - 30)
LI/SS	147 A8

Dimensions US Standard

Usa code	94005147
Ply Rating	14
Section Width (inch)	18.7
Overall Diameter (inch)	60.2
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	173
Rim Rec	DW 16 L
Rim Alt	DW 15 L
TRA Code	R3

Load capacity (lbs)

mph / psi	38
25	6780

Printed on 25/04/2024 10:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..