

## TR 387 - Especificações técnicas



### Description

TR 387 é um pneu agro-industrial, apropriado para reboques para canas-de-açúcar e compactadores. O pneu destaca-se pela elevada capacidade de carga e está disponível em várias versões, com vista a atender às exigências específicas dos utilizadores em termos de resistência a cortes e rasgões, operações de serviço pesado e duração. A versão "dual bead", de talão duplo, é apropriada particularmente para tratores industriais e operações de transporte com reboques.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

Industrial: Compactador

Version	DUAL BEAD HD
Type	TL
Tyre Size	23.1 - 26
LI/SS	157 A8

## Dimensions US Standard

Usa code	94030682
Ply Rating	18
Section Width (inch)	23.3
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	184.6
Rim Rec	DW 20 B
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	9090

Printed on 25/04/2024 07:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..