

## TR 390 - Especificações técnicas



### Description

TR 390 é um pneu agro-industrial, apropriado para reboques para canas-de-açúcar e compactadores. O pneu TR 390 destaca-se pela elevada capacidade de carga e pela durabilidade acrescida. A sua versão "dual bead HD", de talão duplo HD, é apropriada particularmente para os tratores industriais e para as operações de transporte com reboques, enquanto a versão "dual bead HD special", de talão duplo HD especial, é apropriada para operações de serviço pesado.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Reboque

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	28L - 26
LI/SS	154 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	714
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4545
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-004608
TRA Code	R3

## Load capacity (Kg)

km/h / bar	1.40
30	3750

Printed on 26/04/2024 11:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..