

TR 390 - Especificações técnicas



Description

TR 390 é um pneu agro-industrial, apropriado para reboques para canas-de-açúcar e compactadores. O pneu TR 390 destaca-se pela elevada capacidade de carga e pela durabilidade acrescida. A sua versão "dual bead HD", de talão duplo HD, é apropriada particularmente para os tratores industriais e para as operações de transporte com reboques, enquanto a versão "dual bead HD special", de talão duplo HD especial, é apropriada para operações de serviço pesado.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Reboque

Industrial: Compactador

Version	DUAL BEAD
Type	TL
Tyre Size	28L - 26
LI/SS	157 A8

Dimensions US Standard

Usa code	94070695
Ply Rating	16
Section Width (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E4-106R-002337
TRA Code	R3

Load capacity (lbs)

mph / psi	28
25	9100

Printed on 26/04/2024 09:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..