

TR 391 - Especificações técnicas



Description

TR 391 é um pneu agro-industrial, apropriado para as operações de transporte e compactação com reboques para canas-de-açúcar e compactadores. TR 391 destaca-se pela elevada capacidade de carga e uma vida operacional mais longa.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Reboque

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	119 A8

Dimensions US Standard

Usa code	94005260
Ply Rating	6
Section Width (inch)	15.9
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.8
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 13 L ; DW 12
TRA Code	R3

Load capacity (lbs)

mph / psi	20
25	3000

Printed on 29/04/2024 08:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..