

TR 393 (B) - Especificações técnicas



Description

TR 393 (B) foi especialmente concebido para semeadores, espalhadores e alfiadas para utilizar na estrada e fora dela. O design especial do rasto proporciona melhores propriedades de flutuação e autolimpeza, para além de uma longa vida útil. Graças à sua grande área de contacto, o TR 393 (B) assegura uma excelente tração e minimiza a compactação do solo.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Espalhador

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions US Standard

Usa code	94070626
Ply Rating	12
Section Width (inch)	13.8
Overall Diameter (inch)	30.6
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

Load capacity (lbs)

mph / psi	75
30	3520

Printed on 29/04/2024 14:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..